

Basic Model <sup>1</sup>	Fatigue Rated Model	Hold-Down Bolts	Torque Ft-Lbs	Loading Bolt	Torque Ft-Lbs
FL025U(C)		#10-32NF	1.25	1/4-20NC	3
FL05U(C)		#10-32NF	1.25	1/4-20NC	3
FL1U(C)		#10-32NF	1.25	5/16-18NC	6
FL2.5U(C)		#10-32NF	2.5	3/8-16NC	16
	FFL(1.8/±1.2)U(C)	#10-32NF	2.5	3/8-16NC	16
FL5U(C)		#10-32NF	5.0	7/16-20NF	50
FL7.5U(C)		#10-32NF	6.0	7/16-20NF	60
FL10U(C)		1/4-28NF	11.0	5/8-18NF	130
	FFL(4.5/±3)U(C)	1/4-28NF	11.0	7/16-20NF	60
	FFL(7.5/±5)U(C)	1/4-28NF	11.0	5/8-18NF	130
FL25U(C)		3/8-24NF	35	1-14NF	450
	FFL(15/±10)U(C)	3/8-24NF	35	1-14NF	450
FL35U(C)		7/16-20NF	55	1-1/4-12N	750
	FFL(22.5/±15)U(C)	7/16-20NF	55	1-1/4-12N	750
FL50U(C2)		1/2-20NF	90	1-1/2-12N	1,340
	FFL(30/±20)U(C2)	1/2-20NF	90	1-1/2-12N	1,340
FL75U(C1)		3/4-16NF	270	1-3/4-12N	2,200
	FFL(45/±30)U(C1)	3/4-16NF	270	1-3/4-12N	2,200
FL100U(C)		3/4-16NF	270	2-12N	3,300
	FFL(60/±40)U(C)	3/4-16NF	270	2-12N	3,300
FL150U(C)		3/4-16NF	270	2-3/8-12N	6,000
	FFL(99/±66)U(C)	3/4-16NF	270	2-3/8-12N	6,000
FL200U(C)		3/4-16NF	270	2-3/8-12N	7,700
	FFL(120/±80)U(C)	3/4-16NF	270	2-3/8-12N	7,700
FL300U(C)		1-14NF	560	3-12N	14,600
	FFL(180/±120)U(C)	1-14NF	560	3-12N	14,600
FL400U(C)		1-1/8-12NF	800	3-1/2-8N	23,000
	FFL(270/±180)U(C)	1-1/8-12NF	800	3-1/2-8N	23,000